

Kodak i1200 series scanners



Meet all your workgroup needs with an easy-to-use scanner that fits just about anywhere.

Small, powerful and packed with features and benefits, the **Kodak** i1210 and i1220 scanners deliver on your desktop scanning needs. They can auto-feed almost anything at speeds up to 30 pages per minute, including documents as small as an identification card or as long as 863 mm (34 in.). The i1200 series scanners provide you with a wide range of output options—including searchable PDF files for easy information access.

All the ease of use and versatility you're looking for—no matter what the job is.

Our smart touch feature enables you to select the right scanning application for the job. With the touch of a button, scan documents to:

- File
- E-mail
- Printers

- Other desktop applications that support TIFF, JPEG, RTF, PDF and searchable PDF

In addition, these powerful scanners have a unique tilt-and-scan feature that allows you to select the best scanning position for the job:

- Flat with trays extended for higher-volume batch scanning
- Fully upright with the input tray folded down for ad hoc and transaction scanning (you can even position the scanner up against a wall and still auto-feed documents)

There's also an optional tethered flatbed scanner (A4 size) for more convenience and flexibility. Simply attach the flatbed and scan your exception documents at up to 1200 dpi optical resolution. Then just unplug and store the flatbed. It's that easy!

Get exceptional image quality

It starts with 600 dpi optical resolution for razor-sharp images. But we didn't stop there. These compact machines feature

enhanced Perfect Page image processing for outstanding image quality that's virtually automatic. No need for rescans!



Enjoy unique value

With all this capability, affordable pricing and the peace of mind that comes with **Kodak** Service & Support, the i1210 and i1220 scanners deliver an extraordinary combination of performance and value.

Kodak i1200 series scanners

Recommended Daily Volume	Up to 1,500 pages per day
Throughput Speeds (portrait, letter size)	Bitonal/grayscale/color: Up to 30 ppm/60 ipm at 200 dpi (Throughput speeds may vary depending on your choice of driver, application software, operating system and PC.)
Scanning Technology	i1210: Single CCD; i1220: Dual CCD; Grayscale output bit depth is 256 levels (8-bit) Color capture bit depth is 48 bits (16 x 3); Color output bit depth is 24 bits (8 x 3)
Optical Resolution	600 dpi (i1210/i1220); 1200 dpi (A4 Flatbed Accessory)
Illumination	Dual fluorescent (cold cathode)
Output Resolution	75, 100, 150, 200, 240, 300, 400, 600 and 1200 dpi
Maximum/Minimum Document Size	215 mm x 863 mm (8.5 in. x 34 in.)/50 mm x 63.5 mm (2.0 in. x 2.5 in.)
Paper Thickness and Weight	34-413 g/m ² (9-110 lb.) paper; ID card thickness: up to 1.25 mm (0.05 in.)
Feeder	Up to 50 sheets of 75 g/m ² (20 lb.) paper, handles small documents, such as ID cards, embossed cards and insurance cards
Multi-feed Detection	With ultrasonic technology
Connectivity	USB 2.0
Bundled Software	TWAIN and ISIS drivers; Kodak Capture Software, Lite ; Nuance ScanSoft OmniPage 14 and PaperPort 10 (or PaperPort Deluxe 9 Asian for China, Hong Kong, Japan, Korea and Taiwan)
Imaging Features (in the scanner)	Perfect Page Scanning; iThresholding; adaptive threshold processing; deskew; autcrop; relative cropping; aggressive cropping; electronic color dropout; dual stream scanning; interactive color, brightness and contrast adjustment; auto orientation; automatic color detection; background color smoothing
File Format Outputs	Single and multi-page TIFF, JPEG, RTF, PDF, searchable PDF
Warranty (US and Canada)	One-year warranty
Accessories	Kodak white imaging background accessory (front); Kodak A4 Flatbed Accessory with 1.8-meter (6 ft.) cable; Optional flatbed black imaging background accessory
Electrical Requirements	100-240 V (International); 50-60 Hz
Power Consumption	i1210: Sleep mode: <6 Watts; Running: <35 Watts, i1220: Sleep mode: <6 Watts; Running: <40 Watts
Environmental Factors	Energy Star qualified scanners, Operating temperature: 15-35° C (59-95° F), Operating humidity: 15% to 76% RH
Acoustical Noise (operator position Sound Pressure level)	Standby mode: <30 dB(A) Operating mode: <58 dB(A)
Recommended PC Configuration	For documents up to 356 mm (14 in.) long at 400 dpi: Pentium IV , 3.2 GHz processor, 512 MB RAM For documents up to 660 mm (26 in.) long at 400 dpi: Pentium IV , 3.2 GHz processor, 1 GB RAM For longer documents/higher resolutions: Pentium IV , 3.2 GHz processor, 3 GB RAM
Supported Operating Systems	Windows XP SP2 (supports USB 2.0); Windows XP 64-bit edition , Windows 2000 Professional (supports USB 2.0)
Approvals and Product Certifications	AS/NZS 3548 Class B (C-Tick Mark), CAN/CSA-C22.2 No. 60950-1-03 (C-UL Mark), Canada ICES-003 Issue 3 (Class B), GB4943, GB9254 (Class B), GB 17625.1 Harmonics (CCC "S&E" Mark), EN 55022 ITE Emissions (Class B), EN 61000-3-3 Flicker, EN 55024 ITE Immunity, (CE Mark), EN 60950 (TUV GS Mark), IEC 60950, CISPR 22 (Class B), VCCI (Class B), CNS 13438 (Class B), CNS 14336, (BSMI Mark), UL 60950-1 (UL Mark), CFR 47 Part 15 Subpart B (FCC Class B), Argentina S-Mark
Consumables Available	Feed Module, Separation Module, Feed Rollers, Roller Cleaning Pads, Staticide Wipes
Dimensions	Weight: i1210: 5.2 kg (11.5 lbs.), i1220: 5.5 kg (12.0 lbs.) Depth: 162 mm (6.3 in.) not including input tray and output tray Width: 330 mm (13.0 in.) Height: 246 mm (9.7 in.) not including input tray

To learn more:

www.kodak.com/go/i1200

Keep it Simple. Keep it Kodak.

Printed using Kodak technology.

Eastman Kodak Company

343 State Street, Rochester, NY 14650
1-800-944-6171

Kodak Canada, Inc.

Toronto, Ontario M6M 1V3
1-800-465-6325

Kodak GmbH Hedelfingerstr 60

70327 Stuttgart, Germany
EAMER-DI-Capture@kodak.com

Kodak (Australasia) Pty. Ltd.

North Ryde NSW 2113 Australia
61-2-9870-4224

Kodak (Hong Kong) Limited

North Point, Hong Kong 07021
852-2564-9330

Kodak Japan Limited

Tokyo, Japan
81-3-5540-2270
jp-di-mktg@kodak.com

Kodak de Mexico

Mariano Otero 408 Guadalajara, Mexico
(52) (33) 3818-6598

For other areas outside the U.S.A.,
call +1-585-722-9287



As an **Energy Star**® Partner, Eastman Kodak Company has determined that these products meet **Energy Star**® guidelines for energy efficiency.



©Kodak, 2006. Kodak is a trademark of Kodak.

Specifications are subject to change without notice.

A-5760 CAT No. 888 4983 Printed in USA 06/06

Kodak